



DEX III ATF

(July 2021 edition)

AMALIE DEX III ATF is formulated for older model Ford and General Motors vehicles requiring MERCON®, DEXRON-I®, DEXRON-II® and DEXRON-III®. It is recommended for use in all transmissions, hydraulic systems, and power steering units manufactured by American, European, Korean, Japanese and other manufactures from around the world specifying DEXRON®III / MERCON® and earlier DEXRON® / MERCON® type transmission fluids.

Check owner's manual for specific recommendations.

Benefits

- Prevents Corrosion
- Controls Foam
- Safe for Seals
- Promotes Smooth Shifting

Typical Physical and Chemical Properties

Kinematic Viscosity @100°C, cSt.....	7.2
Kinematic Viscosity @40°C, cSt.....	34.5
Viscosity Index.....	170
Color.....	Red (6.5)
Specific Gravity.....	0.860
Flash Point, °C	200
Pour Point, °C	-48
Brookfield Viscosity @(-40°C) cP.....	<20,000
Copper Corrosion.....	1b

Typical values are listed.

Applications

SPECIFICATIONS	DEX III
DEXRON®, DEXRON® II, III H	√
MERCON®	√
Allison C3, C4, TES 389B	√
Caterpillar TO-2	√
Volvo 97341	√
MB (Where DEXRON III type fluids are specified)	√
MAN (Where DEXRON III type fluids are specified)	√
ZF TE-ML 14A, 04D, 17C, 03D	√
VOITH H55.6355.XX	√
Power Steering Units **	√

** Calling for a fluid listed in the above table.

ADDITIONAL INFORMATION

Please use proper handling and care that you would use with any motor oil. Contact your Sales Representative for SDS.