

# TECHNICAL DATA SHEET

## **AMALIE Elixir Full Synthetic 0W-16**

(05/17/21 edition)

AMALIE Elixir Full Synthetic SAE 0W-16 is a premium full synthetic motor oil blended with high-quality synthetic base stocks, a shear stable viscosity modifier, and the latest additive technology to provide the ultimate protection & performance for a wide range of vehicle demands. Specifically formulated for the rigorous environment of gas-direct engine (GDI) and turbo gas-direct engine (TGDI) designs as well as providing increased protection for carbureted or normally fuel injected engines. It contains additive technology designed to prevent low-speed pre-ignition (LSPI). LSPI can lead to premature engine failure and is a major concern of engine manufacturers.

<u>AMALIE Elixir Full Synthetic SAE 0W-16</u> is formulated to exceed the latest API SP engine oil category as well as ILSAC GF-6B. It delivers superior performance for wear control, deposit control, oxidative stability, piston cleanliness, and timing chain wear over previous API categories as well as conventional and synthetic blended oils.

### Benefits:

- Outstanding Thermal and Oxidation Stability.
- Excellent Sludge and Varnish Protection.
- Formulated to Prevent LSPI.
- Volatility: Lowers Oil Vaporization and Consumption at Extreme Conditions.
- Increased Wear Protection Over Previous Oil Categories.

Typical values are listed. Variations not affecting the performance of this fluid may occur during production.

## **Typical Physical and Chemical Properties**

| Viscosity Grade                       | . SAE 0W-16 |
|---------------------------------------|-------------|
| Kinematic Viscosity @100°C, cSt       | 7.3         |
| Kinematic Viscosity @ 40°C, cSt       | 37.0        |
| Viscosity Index                       | 168         |
| Cold Cranking Viscosity, cP @ (-35°C) | .5350       |
| Flash Point, °C (°F)                  | 210 (410)   |
| Pour Point, °C (°F)                   | 45 (-44)    |
| HT/HS Viscosity, cP                   | 2.4         |
| TBN, mgKOH/g                          | 8.0         |
| Noack Volatility, %weight loss        | 12.0        |
|                                       |             |

### **Applications**

AMALIE Elixir Full Synthetic 0W-16 meets the performance requirements of API SP, ILSAC GF-6B, Honda, Toyota, Nissan, American or European Manufacturers recommending a SAE 0W-16 oil.

### **Health and Safety**

Safety Data Sheets (SDS) are available from your sales representative or at AMALIE.com.

<sup>\*</sup>Always refer to your vehicles operating manual to select the correct grade oil for your engine.