

Hypoid Gear Multi-Purpose GL-5 75W Gear Oil

(October 2021 edition)

AMALIE Hypoid Gear Multi-Purpose GL-5 75W Gear Oil is a premium gear lubricant designed for passenger vehicles and light-duty commercial axles, and final drives. Features include excellent thermal and oxidation stability, compatibility with seal materials, water separation, foam suppression, and superior storage stability.

Benefits

- > Excellent EP and Anti-Wear Properties
- > Strong Resistance to Oxidation
- > Protects Against Rust and Corrosion
- Excellent Demulsibility
- > Compatibility with Seal Materials

Typical Physical and Chemical Properties

| Viscosity Grade | 75W |
|---------------------------------|----------|
| Kinematic Viscosity @100°C, cSt | 6.5 |
| Kinematic Viscosity @40°C, cSt | 42 |
| Viscosity Index | 105 |
| Flash Point, °C (°F) | 218(424) |
| Pour Point, °C (°F) | 42(-43) |
| Density, S.G | 0.87 |
| Brookfield Viscosity, -40°C, cP | 75,000 |

Typical values are listed. Variations not affecting the performance of this fluid may occur during production; however, these variations will not fall outside of set specification parameters.

Recommendations

AMALIE Hypoid Gear Multi-Purpose GL-5 75W Gear Oil is recommended for gear boxes and transaxles that call for GL-5 gear oil.

Health and Safety

Safety Data Sheets (SDS) are available online at AMALIE.com or from your AMALIE Representative.