

# TECHNICAL DATA SHEET

## **AMALIE Heavy Duty 40**

(05-17-21 edition)

<u>AMALIE Heavy Duty 40</u> provides shear stability and excellent engine protection. It is designed for use in passenger cars where the use of API SP, SN Plus, SN, SM or SL engine oils are required. The AMALIE Heavy Duty 40 is formulated to provide piston cleanliness, LSPI control, chain wear protection, and oil thickening control for engines that require a straight weight oil.

Always consult your vehicle's owner's manual when selecting the appropriate viscosity and service grade.

#### Benefits:

- Shear Stable.
- > Improved LSPI Control.
- > Added Chain Wear Protection.
- Promotes Engine Cleanliness.
- Compatible with Conventional and Synthetic Engine Oils.

### **Typical Physical and Chemical Properties**

Viscosity Grade	SAE 40
Kinematic Viscosity @ 100°C, cSt	13.8
Kinematic Viscosity @40°C, cSt	.130.0
Viscosity Index	102
TBN, mg/KOH/g	7.5
Flash Point, °C (°F)	.230 (446)
Pour Point, °C (°F)	33 (-27)
Density, S.G	.0.88
Sulfated Ash, wt%	.0.68

Typical values are listed. Variations not affecting the performance of this fluid may occur during production however; these variations will not fall outside of set specification parameters.

### **Applications**

AMALIE Heavy Duty 40 is for use in passenger cars where API SP, SN Plus, SN, SM / CF, or previous category engine oils are recommended. It may also be used for gear or hydraulic applications where the OEM has recommended the use of a straight weight detergent oil.

#### **Health and Safety**

Safety Data Sheets (SDS) are available on line at AMALIE.com or from your AMALIE Representative.