



AMALIE PRO High Performance Synthetic Blend 15W-50

(05/17/21 edition)

AMALIE PRO High Performance Synthetic Blend 15W-50 is formulated to exceed the latest API SP engine oil categories. A blend of high viscosity index oils, synthetic base stocks, shear stable viscosity modifiers and the latest additive technology, it is specifically formulated for the rigorous environment of gas-direct engine (GDI) and turbo gas-direct engine (TGDI) designs as well as providing increased protection for carbureted or normally fuel injected engines. AMALIE PRO High Performance Synthetic Blend 15W-50 offers improved performance for wear control, oxidative stability, piston cleanliness, and chain wear over previous API oil categories as well as conventionally formulated oils.

Always consult your vehicle's owner's manual when selecting the appropriate viscosity and service grade.

Benefits:

- Extended Engine Protection in Severe Operating Conditions.
- LSPI (Low Speed Pre-Ignition) Protection Throughout the Drain Interval.
- GPF (Gas Particulate Filter) Compatible.
- Reduced Oil Thickening & Consumption.
- Superior Wear Protection.
- Enhanced Deposit Control and Engine Cleanliness.

Typical Physical and Chemical Properties

Viscosity Grade.....	15W-50
Kinematic Viscosity @100°C, cSt.....	17.75
Kinematic Viscosity @40°C, cSt.....	140.4
Viscosity Index.....	140
Cold Cranking Viscosity, cP @ (-20°C).....	6600
Flash Point, °C (°F).....	225 (437)
Pour Point, °C (°F).....	-36 (-32.8)
Density, S.G.....	0.874
MRV, cP @ (-25°C)	30,000

Typical values are listed. Variations not affecting the performance of this fluid may occur during production.

Applications

Recommended for Service fill applications for Ford, Chrysler, GM, Honda, Toyota, Hyundai, Nissan, and other Asian or European brands when 15W-50 API SP, SN / SN Plus, SN, SM/CF or previous category engine oil is specified.

Health and Safety

Safety Data Sheets (SDS) are available on line at AMALIE.com or from your AMALIE Representative.