



XLO Heavy Duty Fleet 10W Engine Oil

(July 2021 edition)

AMALIE XLO Heavy Duty Fleet 10W Engine Oil is high quality detergent motor oil recommended for diesel and gasoline engines manufactured by American, European, Korean, Japanese and other engine manufacturers from around the world. These oils are formulated to meet the requirements of API CF-2, CF as well as earlier API diesel engine oil categories. They are manufactured from select blends of high quality base oils and additives to promote long engine life and protection against rust, corrosion and harmful oxidation. **AMALIE XLO Heavy Duty Fleet 10W Engine Oil** is designed to help reduce engine wear and oil consumption. **AMALIE Fleet 10W** may also be used in hydraulic systems where mono-grade engine oil is specified.

Always consult your vehicle's owner's manual when selecting the appropriate viscosity and service grade.

Benefits

- Low Ash Content
- Improved Sludge Control
- Excellent Protection for Metal Components from Rust, Corrosion and Wear
- Superior Protection Across a Wide Temperature Operating Range
- Suitable for Mixed Fleets

Typical Physical and Chemical Properties

| | |
|---|-----------|
| Viscosity Grade..... | 10W |
| Kinematic Viscosity @100°C, cSt..... | 7.0 |
| Kinematic Viscosity @40°C, cSt..... | 46.0 |
| Viscosity Index..... | 110 |
| Cold Cranking Viscosity, cP @ (25°C)..... | 6300 |
| Flash Point, °C (°F)..... | 220(428) |
| Pour Point, °C (°F)..... | -30 (-22) |
| Density, S.G..... | 0.8720 |
| TBN, mgKOH/g..... | 7.5 |

Typical values are listed. Variations not affecting the performance of this fluid may occur during production however; these variations will not fall outside of set specification parameters.

Approvals and Recommendations

API CF and all previous categories

Please consult AMALIE Technical Services or your local representative for a full listing of applications.