

AMALIE

Better than it has to be[®]
Since 1903



DOT 3 BRAKE FLUID

AMALIE DOT 3 Brake Fluid performs a variety of important functions in braking systems. It transmits the required power, minimizes corrosion, lubricates, controls proper seal swelling, and operates over a wide temperature range. **AMALIE DOT 3 Brake Fluid** meets or exceeds the requirements of FMVSS No 571 116 DOT 3, SAE J1704, and ISO 4925. **AMALIE DOT 3 Brake Fluid** has a minimum boiling point (ERBP) of 475 F. This fluid controls corrosion and maintains proper seal longevity and performance.

Benefits:

- Wet and Dry Boiling Points
- Miscibility with All Allied DOT 3 Brake Fluids
- Corrosion Protection
- Compatibility with Natural and Synthetic Rubber Seals Used in Braking Systems
- Long-Term Stability

DOT 4 BRAKE FLUID

AMALIE DOT 4 Brake Fluid performs a variety of important functions in braking systems. It transmits the required power, minimizes corrosion, lubricates, controls proper seal swelling, and operates over a wide temperature range. **AMALIE DOT 4 Brake Fluid** meets or exceeds the requirements of FMVSS No 571 116 DOT 4, SAE J1704, and ISO 4925. **AMALIE DOT 4 Brake Fluid** has a minimum boiling point (ERBP) of 475 F. This fluid controls corrosion and maintains proper seal longevity and performance.

Benefits:

- Wet and Dry Boiling Points
- Miscibility with All Allied DOT 3 Brake Fluids
- Corrosion Protection
- Compatibility with Natural and Synthetic Rubber Seals Used in Braking Systems
- Long-Term Stability

POWER STEERING FLUID

AMALIE Power Steering Fluid is formulated using highly refined base oils and select additives to provide year-round smooth and reliable performance. It provides optimum protection and service in power steering systems of both foreign and domestic vehicles.

AMALIE Power Steering Fluid helps to control seal swelling and protects pump parts against wear while providing the proper frictional properties for optimum performance. It is designed to protect against wear, oxidation and corrosion as well as protecting against foaming, clogging and rust. It will not harm rubber hoses. This product is blended to mix with original equipment fluids.

FULL STRENGTH ANTIFREEZE COOLANT

AMALIE Antifreeze / Coolant is a conventional formula designed for fleet heavy-duty cooling system applications without the need for a "pre-charge" of supplemental coolant additive (SCA). It contains a blend of ethylene glycol pre-charged with heavy-duty chemical additives. This is a nitrite containing non-carboxylic acid formulation. This formulation will protect diesel engines against liner pitting and scale deposits from hard water minerals. The formulation's chemistry affords all metals protection from corrosion and is compatible with most major brands of coolant. **AMALIE Antifreeze / Coolant** can be used in both diesel engine and light duty gasoline engine applications. The product does not require a charge of supplemental coolant additives (SCA) during initial fill or if the coolant is totally replaced.

Always consult your vehicle's owner's manual when selecting the appropriate Antifreeze/Coolant.

Benefits:

- Fully formulated
- Amine and phosphate free
- Hard water compatible
- Excellent liner cavitation protection
- Excellent high temperature aluminum protection
- Prevents corrosion of brass, copper, solder, steel, cast iron and aluminum
- Coolant is miscible and compatible with other traditional fully formulated coolant products
- Compatible with standard heavy duty SCAs and coolant filters
- Suitable for up to 3,000 hours or 150,000 miles in heavy duty application under normal operating conditions
- Available as a 50/50 Premix

50/50 PRE-DILUTED ANTIFREEZE COOLANT

AMALIE 50/50 Pre-Diluted Antifreeze is a conventional formula designed for fleet heavy-duty cooling system applications without the need for a "pre-charge" of supplemental coolant additive (SCA). It contains a blend of ethylene glycol pre-charged with heavy-duty chemical additives. This is a nitrite containing non-carboxylic acid formulation. This formulation will protect diesel engines against liner pitting and scale deposits from hard water minerals. The formulation's chemistry affords all metals protection from corrosion and is compatible with most major brands of coolant. **AMALIE 50/50 Pre-Diluted Antifreeze** can be used in both diesel engine and light duty gasoline engine applications. The product does not require a charge of supplemental coolant additives (SCA) during initial fill or if the coolant is totally replaced.

Always consult your vehicle's owner's manual when selecting the appropriate Antifreeze/Coolant.

Benefits:

- Fully formulated
- Amine and phosphate free
- Hard water compatible
- Excellent liner cavitation protection
- Excellent high temperature aluminum protection
- Prevents corrosion of brass, copper, solder, steel, cast iron and aluminum
- Coolant is miscible and compatible with other traditional fully formulated coolant products
- Compatible with standard heavy duty SCAs and coolant filters
- Suitable for up to 3,000 hours or 150,000 miles in heavy duty application under normal operating conditions



MADE IN U.S.A.

BRAKE FLUID

VISCOSITY	PACK SIZE	PART #
DOT 3	12-12 Ounce	160-65031-92
	12-1 Quart	160-65036-50
	4-1 Gallon	160-65037-36
DOT 4	55 Gallon Drum	160-65033-05
	12-12 Ounce	160-65041-92
	12-1 Quart	160-65046-50
	55 Gallon Drum	160-65043-05

POWER STEERING FLUID

VISCOSITY	PACK SIZE	PART #
	12-12 Ounce	160-65181-92
	55 Gallon Drum	160-65183-05



ANTIFREEZE COOLANT

VISCOSITY	PACK SIZE	PART #
FULL STRENGTH	4-1 Gallon	160-65327-36
	55 Gallon Drum	160-65323-05
50/50 PRE-DILUTED	4-1 Gallon	160-65357-36
	55 Gallon Drum	160-65353-05

Always refer to your vehicles operating manual to select the correct grade of oil for your engine. The data presented herein are believed to be accurate; however, Amalie Oil Company shall not be liable for its content and makes no warranty with respect thereto.

