





AMALIE Super XLO Ultimate Full Synthetic Molybdenum Fortified Motor Oil is a full synthetic high-performance diesel engine oil utilizing the latest in additive technology to offer the ultimate protection of your engine. Designed to meet or exceed the latest OEM and API CK-4 requirements, it is also backwards compatible to previous OEM and API specifications such as CJ-4, Cl-4, Cl-4+, and CH-4. It carries the API SN classification for use in gasoline engines and is an excellent choice for operators with mixed fleets. This oil is specially designed to protect EGR/Low-Emission Diesel Engines while maximizing the durability of Diesel Particulate Filters (DPF's).

AMALIE Super XLO Ultimate Full Synthetic Molybdenum Fortified Motor Oil is recommended for use in a wide range of heavy-duty applications and operating environments found on-and off-highway, including engines operating under heavy loads. It is formulated for extended service/extended drain when operated under typical operating conditions. It offers improved TBN retention, lower oil consumption, greater wear protection, oxidation stability, excellent shear stability, and reduced high temperature deposits.

Benefits:

- Excellent Protection for Metal Components from Rust, Corrosion and Wear High Soot Handling
- Improved Sludge Control Superior Oxidation Stability Shear Stable Formulation Lasting TBN Retention
- Exceptional Oil Consumption Control Excellent Low Temperature Pumpability One Oil for Mixed Fleets



MOTOR OIL

AMALIE XLO Synthetic Blend Molybdenum Fortified CK-4 Motor Oils are premium high performance diesel engine oils utilizing the latest in engine oil additive technology and a blend of quality conventional and synthetic base stocks to offer the ultimate protection of your engine. Designed to meet or exceed the latest OEM and API CK-4 requirements, it is also backwards compatible to previous OEM and API specifications such as CJ-4, CJ-4, CJ-4+, and CH-4. This oil is specially designed to protect EGR/Low-Emission Diesel Engines while maximizing the durability of Diesel Particulate Filters (DPF's).

AMALIE XLO Synthetic Blend Molybdenum Fortified CK-4 Motor Oils are recommended for use in a wide range of heavy-duty applications and operating environments found on-and off-highway, including engines operating under heavy loads. It is formulated for extended service/extended drain when operated under typical operating conditions. AMALIE CK-4 motor oils offer improved TBN retention, lower oil consumption, greater wear protection, oxidation stability, excellent shear stability, and reduced high temperature deposits.

AMALIE CK-4 10W-40, 15W-40 and 20W-50 motor oils carry the API SN classification for use in gasoline engines and are excellent choices for operators with mixed fleets.

Benefits:

- Excellent Protection for Metal Components from Rust, Corrosion and Wear
 High Soot Handling
- Improved Sludge Control Superior Oxidation Stability Shear Stable Formulation Lasting TBN Retention
- Exceptional Oil Consumption Control
 One Oil for Mixed Fleets

AMALIE ALAS+ (AMALIE Lubricant Analysis System) is AMALIE's used oil analysis program designed exclusively for AMALIE XLO and AMALIE XLO Ultimate customers. It allows them to get an inside look at what is going on in their engine. ALAS+ measures wear metals, contaminants, viscosity and other used oil characteristics to help prevent component failure, determine optimum drain intervals and help to reduce fuel costs. ALAS+ is a comprehensive analysis program using the most modern laboratory equipment available, that provides valuable information about your engine's condition every time the oil is changed for the life of the equipment. ALAS+ supplies clear concise analytical reports in a timely fashion that include the necessary data needed to help you successfully manage your highly expensive equipment investment.

SUPER XLO ULTIMATE FULL SYNTHETIC

VISCOSITY	PACK SIZE	PART #
5W-40	4-1 Gallon	160-60197-36
	5 Gallon Pail	160-60194-25
	6 Gallon BIB	160-60190-21
	55 Gallon Drum	160-60193-05



XLO ULTIMATE SYNTHETIC BLEND

VISCOSITY	PACK SIZE	PART #
10W-30	4-1 Gallon	160-79177-36
	5 Gallon Pail	160-79174-25
	55 Gallon Drum	160-79173-05
	330 Gallon Tote	160-79178-02
10W-40	4-1 Gallon	160-79187-36
	5 Gallon Pail	160-79184-25
	55 Gallon Drum	160-79183-05
15W-40	12-1 Quart	160-79106-56
	4-1 Gallon	160-79107-36
	3-2.5 Gallon	160-79101-26
	5 Gallon Pail	160-79104-25
	6 Gallon BIB	160-79100-21
	55 Gallon Drum	160-79103-05
	330 Gallon Tote	160-79108-02
20W-50	4-1 Gallon	160-79197-36
	5 Gallon Drum	160-79194-25



Always refer to your vehicles operating manual to select the correct grade of oil for your engine. The data presented herein are believed to be accurate; however, Amalie Oil Company shall not be liable for its content and makes no warranty with respect thereto.