

# Better than it has to be Since 1903

# SAFETY DATA SHEET

#### PRODUCT AND COMPANY INFORMATION **SECTION 1**

Product Name(s): 100% Syn 5W50 UTV

816555081 Product Code(s):

Uses: A petroleum-based lubricant.

Company: **AOCUSA** 

1601 McCloskey Blvd; Tampa FL 33605; USA Address:

Telephone Number: (813) 248-1988 Fax Number: (813) 248-1488

For Hazardous Materials [or Dangerous Goods] Incident (24 hours/day) **Emergency Telephone Number:** 

ChemTel Inc. (800) 255-3924; +1 (813) 248-0585

Date Issued: October 25, 2021 Date Revised: October 25, 2021

This SDS complies with the OSHA Hazard Communication Standard 29CFR1910.1200 as revised in May

2012 (GHS). It may not meet requirements in other countries.

#### **SECTION 2** HAZARDS IDENTIFICATION

**GHS Signal** 

None.

None.

Word: **GHS** 

Not classified as hazardous

Classification:

**GHS Hazard** None.

Statements:

**GHS** Prevention: Response:

Precautionary

None. None. Statements:

> Storage: Disposal:

None. None.

Hazards Not

Otherwise

Classified:

GHS Approximately < 5% of this mixture consists of ingredient(s) of unknown acute toxicity.

Assessment: Approximately < 5% of the mixture consists of ingredient(s) of unknown hazards to the

aquatic environment.

### **SECTION 3 COMPOSITION / INGREDIENTS**

Component	CAS Number	EC Number	Concentration
Petroleum distillates, hydrotreated	64742-54-7	265-157-1	5.0 - 25.0%

Revision Date: October 25, 2021 Page 1 of 9

#### **SECTION 3 COMPOSITION / INGREDIENTS**

heavy paraffinic	Classification: Carc. 1B: H350 (*) Carc. 1B; H350: C ≥ 3.0 % DMSO Repr. 2; H361d: C ≥ 3.0 % DMSO Asp. Tox. 1; H304: Viscosity ≤ 20.5 mm2/s (40°C)			
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	72623-87-1 276-738-4 65.0 - 85.0%  Classification: Carc. 1B: H350 (*)  Carc. 1B; H350: $C \ge 3.0 \%$ DMSO  Repr. 2; H361d: $C \ge 3.0 \%$ DMSO			
	Asp. Tox. 1; H304: Viscosity ≤ 20.5 mm2/s (40°C)			

Note (\*): Components are highly refined and this hazard does not apply.

Other components are either non-hazardous or do not significantly contribute to the hazards of the product. Trade Secret Claims: Specific chemical identity and/or exact percentage (concentration) of components has been withheld as a trade secret.

For the full text of the H-Statements mentioned in this Section, see Section 16.

#### FIRST AID MEASURES **SECTION 4**

In case of contact, immediately flush eyes with plenty of water for at least 15 First Aid - Eyes:

minutes. Get medical attention, if irritation develops.

First Aid - Skin: In case of contact, flush skin with plenty of soap and water while removing

contaminated clothing and shoes. Get medical attention immediately if irritation

develops and/or persists. Wash contaminated clothing before reuse.

First Aid - Ingestion: If swallowed and feel unwell, call a physician or poison control center. DO NOT

> induce vomiting unless directed to do so by a physician or poison control center. If victim is fully conscious, give a cupful of water. Never give anything by mouth to

an unconscious person.

First Aid - Inhalation: If respiratory symptoms or other symptoms of exposure develop, move victim away

> from source of exposure and into fresh air. If symptoms persist, seek immediate medical attention. If victim is not breathing, clear airway and immediately begin

artificial respiration. If breathing difficulties develop, oxygen should be administered by qualified personnel. Seek immediate medical attention.

Important Symptoms / Mild tissue inflammation, nausea.

Effects – Acute and

Delayed:

Advice to Physician: Treat symptomatically.

#### **SECTION 5** FIRE FIGHTING MEASURES

Treat surrounding material. Water spray, dry chemical, carbon dioxide, or Extinguishing Media:

foam is recommended. Carbon dioxide can displace oxygen. Use caution

when applying carbon dioxide in confined spaces.

Specific Hazards: This product is not flammable, but will burn in a fire. This product may give

rise to hazardous vapors in a fire. Vapors/fumes may be irritating, corrosive

and/or toxic.

Protective equipment and

procedures for fire-fighters.

Wear full protective clothing and self-contained breathing apparatus.

Additional Advice: None.

#### ACCIDENTAL RELEASE MEASURES **SECTION 6**

Spill Procedures: Small spills: Wipe up spills with an absorbent towel/material and transfer

Revision Date: February 19, 2021 Page 2 of 9

## SECTION 6 ACCIDENTAL RELEASE MEASURES

into suitable containers for recovery or disposal. Finally flush area with water/soap or an appropriate solvent, as this product is not appreciably

soluble in water alone.

Large spills: Contain spilled material if possible. Pump into suitable and

properly labeled containers.

Personal Precautions: Wear suitable protective clothing and equipment.

Environmental Precautions: Prevent the material from entering drains or water courses. Do not

discharge directly to a water source. Advise Authorities if spillage has entered watercourse or sewer or has contaminated soil or vegetation.

## SECTION 7 HANDLING AND STORAGE

Handling: Wear appropriate personal protection (See Section 8) when handling this material.

The work area should be equipped with a safety shower and eye wash station. If exposed to the liquid, avoid contact with skin and eyes. Wash thoroughly after handling. Avoid breathing vapors, mists or sprays. Use in a well-ventilated area.

Storage: Keep container(s) tightly closed. Use and store this material at room temperature

away from sources of ignition, heat, direct sunlight and hot metal surfaces. Keep

away from any incompatible materials (see Section 10).

Additional Advice: Store in original container. Store as directed by the manufacturer.

## SECTION 8 EXPOSURE CONTROLS AND PERSONAL PROTECTION

Occupational Exposure

Standards:

Exposure limits are listed below, if they exist.

Petroleum distillates, hydrotreated heavy

paraffinic:

(as petroleum distillates – naphtha) NIOSH REL: 350 mg/m3 TWA. NIOSH REL: 1800 mg/m3 STEL. OSHA PEL: 500 ppm (2000 mg/m3).

(as oil mist)

NIOSH REL: 5 mg/m3 TWA. NIOSH STEL: 10 mg/m3 TWA. OSHA PEL: 5 mg/m3 TWA.

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based:

(as petroleum distillates – naphtha) NIOSH REL: 350 mg/m3 TWA. NIOSH REL: 1800 mg/m3 STEL. OSHA PEL: 500 ppm (2000 mg/m3).

(as oil mist)

NIOSH REL: 5 mg/m3 TWA. NIOSH STEL: 10 mg/m3 TWA. OSHA PEL: 5 mg/m3 TWA.

**Engineering Control** 

Measures:

Engineering methods to prevent or control exposure are preferred. Methods include present or personnel englagues, mechanical ventilation (local

include process or personnel enclosure, mechanical ventilation (local

exhaust), and control of process conditions.

Respiratory Protection: A NIOSH certified self-contained breathing apparatus or air purifying

respirator with an organic cartridge may be used under conditions where

airborne concentrations are expected to exceed exposure limits.

Hand Protection: The use of gloves impervious to the specific material handled is advised to

prevent skin contact, possible irritation and skin damage (see glove

manufacturer literature for information on permeability).

Eye Protection: Approved eye protection (safety glasses with side-shields or goggles) to

safeguard against potential eye contact, irritation, or injury is recommended.

## SECTION 8 EXPOSURE CONTROLS AND PERSONAL PROTECTION

Depending on conditions of use, a face shield may be necessary.

Body Protection: Impervious clothing should be worn as needed to prevent skin contact.

## SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Liquid

Color: Light to dark amber

Odor: Characteristic
Odor Threshold: Not available.
pH: Not available.

Melting Point/Range (°C/°F): -45.0°C / -49.0°F (pour point)

Boiling Point/Range (°C/°F): > 200°C / 392°F (based on constituents)

Flash Point (PMCC) (°C/°F): 230.0°C / 446.0°F

Evaporation Rate: Not available. Flammability / Explosivity Limits in Air (%): Not available.

Vapor Pressure: < 0.075 mmHg (20°C) (based on constituents)

Vapor Density (Air = 1): Not available.

Relative Density: 0.855 g/cm3 (15.6°C)

Solubility in Water: Insoluble

Partition Coefficient: Not available.

Autoignition Temperature (°C/°F): > 250°C / 482°F (based on constituents)

Decomposition Temperature (°C/°F): Not available.

Viscosity: 112.0 mm2/s (40°C)

Explosive Properties: None.

Oxidizing Properties: None.

Volatile Organic Content (VOC) (g/l): 730 - 840 g/l (as defined by 40CFR51.100)

### SECTION 10 STABILITY AND REACTIVITY

Reactivity: Product will not undergo additional reaction.
Stability: Stable under normal storage conditions.

Hazardous Polymerization: Will not occur.

Conditions to Avoid: Contact with incompatible materials, excessive heat.

Incompatibilities: Strong oxidizing agents.

Hazardous Decomposition Oxides of carbon, oxides of sulfur, oxides of phosphorus, metal oxides, aliphatic and aromatic compounds, toxic by-products.

### SECTION 11 TOXICOLOGICAL INFORMATION

If available, toxicity data for the product is given; otherwise component data is listed.

Acute Toxicity: This product is not expected to be appreciably harmful.

(Petroleum distillates, hydrotreated heavy paraffinic) Oral LD50 (rat) > 5000

Revision Date: February 19, 2021 Page 4 of 9

## SECTION 11 TOXICOLOGICAL INFORMATION

mg/kg (similar oil); Dermal LD50 (rabbit) > 5000 mg/kg (similar oil); Inhalation LC50 (rat) > 5.53 mg/l (4 hr) (aerosol) (no mortality – similar oil) (Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based) Oral LD50 (rat) > 5000 mg/kg (similar oil); Dermal LD50 (rat) > 5000 mg/kg (similar oil); Inhalation LC50 (rat) 2.18 mg/l (4 hr) (aerosol – similar oil)

Skin Corrosion / Irritation:

The product may be slightly irritating to the skin.

(Petroleum distillates, hydrotreated heavy paraffinic) Mildly irritating to skin (rabbit – similar oil).

(Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based) Slightly irritating to skin (rabbit – similar oil).

Serious Eye Damage / Irritation:

The product may be slightly irritating to the eyes.

(Petroleum distillates, hydrotreated heavy paraffinic) Non-irritating to eyes (rabbit – similar oil).

(Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based) Slightly irritating to eye (rabbit – similar oil).

Respiratory or Skin Sensitization:

The product is not expected to be dermally sensitizing.

(Petroleum distillates, hydrotreated heavy paraffinic) Not dermally sensitizing (guinea pig – similar oil).

(Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based) Not dermally sensitizing (guinea pig – similar oil).

Mutagenicity:

This product is not expected to be mutagenic.

(Petroleum distillates, hydrotreated heavy paraffinic) Not mutagenic (in vitro mammalian chromosome aberration test and micronucleus assay - similar oil).

(Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based) Not mutagenic (Ames test, in vitro mammalian chromosome aberration test, mammalian cell gene mutation assay and micronucleus assay – similar oils).

Carcinogenicity:

This product is not expected to be carcinogenic.

(Petroleum distillates, hydrotreated heavy paraffinic) Carcinogenic potential is reduced for highly refined distillates. Tumors have developed in animal studies, but were dependent on the concentration of impurities. Not classified as to carcinogenicity to humans (IARC – Petroleum solvents).

(Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based) In a 78 week study in mice by dermal application (0.25 ml dose rate applied once or twice a week), it was shown that there was no carcinogenic potential in sufficiently refined oil. Not classified as to carcinogenicity to humans (IARC – Petroleum solvents).

Reproductive / Developmental Toxicity:

This product is not expected to be reproductively or developmentally harmful. (Petroleum distillates, hydrotreated heavy paraffinic) Reproductive performance and offspring development were not adversely affected in mice or rats (1000 mg/kg – similar oil).

(Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based) In dermally-exposed rats at up to 1000 mg/kg/day during gestation, the developmental NOAEL was determined to be 125 mg/kg/day based on decreased fetal body weights and skeletal anomalies at the highest dose (similar oil).

Chronic/Subchronic Toxicity: Specific Target Organ/Systemic Toxicity – Single Exposure: (Petroleum distillates, hydrotreated heavy paraffinic) No data.

(Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based) No data.

Chronic/Subchronic Toxicity: Specific Target Organ/Systemic Toxicity – (Petroleum distillates, hydrotreated heavy paraffinic) In a 13-week oral study in rats at up to 500 mg/kg/day, the LOAEL was 125 mg/kg/day based on organ weight changes, reddening/discoloration of organs and atrophy in

## SECTION 11 TOXICOLOGICAL INFORMATION

Repeated Exposure: male sex organs (similar oil).

(Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based) In a 13-week oral study in rats at up to 500 mg/kg/day, the LOAEL was 125 mg/kg/day based on organ weight changes, reddening/discoloration of organs and

atrophy in male sex organs (similar oil).

Aspiration Hazard: This product does not pose an appreciable aspiration hazard.

Additional Information: None.

# **SECTION 12 ECOLOGICAL INFORMATION**

If available, ecological data for the product is given; otherwise component data is listed.

Acute Ecotoxicity: This product is not expected to be appreciably harmful to aquatic species.

(Petroleum distillates, hydrotreated heavy paraffinic) LL50 (Fathead minnow) > 100 mg/l/96 hr (similar oil); EL50 (Daphnia magna) > 10000 mg/l/48 hr (similar oil); NOEL (algae) > 100 mg/l/72 hr (similar oil). (Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based) LL50 (fathead minnow) > 100 mg/l/96 hr; EL50 (Daphnia magna) > 10000 mg/l/

48 hr; NOEL (algae) ≥ 100 mg/l/72 hr.

Mobility: (Petroleum distillates, hydrotreated heavy paraffinic) Not expected to be

mobile in soil.

(Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based) Not

expected to be mobile in soil.

Persistence/Degradability: (Petroleum distillates, hydrotreated heavy paraffinic) Not inherently

biodegradable (2-4% in 28 days - similar oil).

(Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based) Not

readily biodegradable (2-4% in 28 days).

Bioaccumulation: (Petroleum distillates, hydrotreated heavy paraffinic) May contain

constituents with the potential to bioaccumulate.

(Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based) No

data.

Other adverse effects: None.

### SECTION 13 DISPOSAL CONSIDERATION

Environmental precautions: Prevent the material from entering drains or water courses. Do not

discharge directly to a water source. Advise Authorities if spillage has entered watercourse or sewer or has contaminated soil or vegetation.

Product Disposal: Dispose in accordance with all local, state (provincial), and federal

regulations. Under RCRA, it is the responsibility of the product's user to determine at the time of disposal, whether the product meets RCRA criteria for hazardous waste. This is because the product uses, transformations, mixtures, processes, etc. may render the resulting materials hazardous.

Container Disposal: Do not remove label until container is thoroughly cleaned. Empty

containers may contain hazardous residues. This material and its

container must be disposed of in a safe way.

### SECTION 14 TRANSPORT INFORMATION

DOT (US):

Proper Shipping Name: Not regulated

UN Number: None.

Revision Date: February 19, 2021 Page 6 of 9

# SECTION 14 TRANSPORT INFORMATION

Class: None.
Packaging Group: None.
Reportable Quantity: None.
Marine Pollutant: None.

IATA:

Proper Shipping Name: Not regulated

UN Number: None.

Class: None.

Packing Group: None.

IMDG:

Proper Shipping Name: Not regulated

UN Number: None.

Class: None.

Packing Group: None.

Marine Pollutant: None.

Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations.

### SECTION 15 REGULATORY INFORMATION

**US Toxic Substance Control** 

Act:

All components of this product are in compliance with the inventory listing requirements of the U.S. Toxic Substances Control Act (TSCA)

Chemical Substance Inventory.

Canadian Domestic Substance

List:

All components of this product are listed on the Canadian Domestic

Substance List.

EU REACh: One or more components of this product may not have been pre-listed or

registered under REACh. Limited quantities may be permitted.

TSCA Sec.12(b) Export

Notification:

This product does not contain a chemical at or above de minimis

concentrations which requires reporting.

Canadian WHMIS

Classification:

None.

This product has been classified in accordance with the hazard criteria of the CPR and the SDS contains all of the information required by the

CPR.

Massachusetts Right-To-Know: This product contains materials subject to disclosure under the

Massachusetts Right-To-Know Law:

- Petroleum distillates, hydrotreated heavy paraffinic (as petroleum

distillates)

- Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (as

petroleum distillates)

New Jersey Right-To-Know: This product contains materials subject to disclosure under the New

Jersey Right-To-Know Law:

- Petroleum distillates, hydrotreated heavy paraffinic (as petroleum

distillates)

- Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (as

petroleum distillates)

## SECTION 15 REGULATORY INFORMATION

Pennsylvania Right-To-Know: This product contains materials subject to disclosure under the

Pennsylvania Right-To-Know Law:

- Petroleum distillates, hydrotreated heavy paraffinic (as petroleum

distillates)

- Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (as

petroleum distillates)

California Proposition 65: This product contains materials which the State of California has found

to cause cancer, birth defects or other reproductive harm:

Benzene (< 18 ppm)</li>Toluene (< 32 ppm)</li>Naphthalene (< 0.8 ppb)</li>

SARA TITLE III-Section 311/312 Categorization (40

CFR 370):

None.

SARA TITLE III-Section 313

(40 CFR 372):

This product does not contain materials which are listed in Section 313

at or above de minimis concentrations.

CERCLA Hazardous Substance (40 CFR 302) This product does not contain materials subject to reporting under

CERCLA and Section 304 of EPCRA.

Water Hazard Class (WGK): This product is slightly water-endangering (WGK=1).

Other Chemical Inventories: Australia (AICS): All components of this product are listed.

China (IECSC): All components of this product are listed.

Japan (ENCS): All components of this product are listed.

Korea (KCI): All components of this product are listed.

Philippines (PICCS): All components of this product are listed.

Taiwan (TCSI): All components of this product are listed.

### **SECTION 16 OTHER INFORMATION**

NFPA Rating - HEALTH: 1

NFPA Rating - FIRE: 1

NFPA Rating - SPECIAL: NONE

Full text of H-Statements referred

NFPA Rating - REACTIVITY:

to under Section 3:

H304 May be fatal if swallowed and enters airways

0

H350 May cause cancer

H361 Suspected of damaging fertility or the unborn child

SDS Date Issued: October 25, 2021

SDS Current Version: 1.0 Version Date: October 25, 2021

SDS Revision History: v1.0 Initial version.

Abbreviations: GHS: Globally Harmonized System of Classification and Labeling of

Chemicals

CAS#: Chemical Abstract Services Number

ACGIH: American Conference of Governmental Industrial Hygienists

OSHA: Occupational Safety and Health Administration

NFPA: National Fire Protection Association DOT: US Department of Transportation

## SECTION 16 OTHER INFORMATION

RCRA: US Resource Conservation and Recovery Act

TLV: Threshold Limit Value
TWA: Time-Weighted Average
PEL: Permissible Exposure Limit
STEL: Short Term Exposure Limit

WEEL: Workplace Environmental Exposure Levels AIHA: American Industrial Hygiene Association

NTP: National Toxicology Program

IARC: International Agency for Research on Cancer

LD50: Lethal Dose 50%

LC50: Lethal Concentration 50%
NOAEL: No Observed Adverse Effect Level
NOEL: No Observed Effect Level

EC50: Effective Concentration 50% LL50: Lethal Loading Rate 50% BCF Bioconcentration Factor BOD: Biological Oxygen Demand

Koc: Soil Organic Carbon Partition Coefficient.

Tlm: Median Tolerance Limit

Key References: United States National Library of Medicine's TOXNET

Patty's Toxicology, 5th Edition

European Commission's Institute for Health and Consumer Protection

European Chemicals Agency (ECHA)

American Conference of Governmental Industrial Hygienists

International Agency for Research on Cancer United States National Toxicology Program

United States Occupational Safety and Health Administration

United States Department of Transportation

Supplier Material Safety Data Sheets

Disclaimer: The data contained herein is based on information that the company

believes to be reliable, but no expressed or implied warranty is made with regard to the accuracy of such data or its suitability for a given situation. Such data relates only to the specific product described and not to such products in combination with any other product and no agent of the company is authorized to vary any of such data. The company and its agents disclaim all liability for any action taken or

foregone on reliance upon such data.

Prepared by: ChemOne Compliance, LLC