

SAFETY DATA SHEET

SECTION 1 PRODUCT AND COMPANY INFORMATION

Product Name(s):	IndGrOil Syn 6800		
Product Code(s):	830906882		
Uses:	A petroleum-based lubricant.		
Company:	AOCUSA		
Address:	1601 McCloskey Blvd; Tampa FL 33605; USA		
Telephone Number:	(813) 248-1988	Fax Number:	(813) 248-1488
Emergency Telephone Number:	For Hazardous Materials [or Dangerous Goods] Incident (24 hours/day)		
	ChemTel Inc. (800) 255-3924; +1 (813) 248-0585		
Date Issued:	May 21, 2020	Date Revised:	October 25, 2021
This SDS complies with the OSHA Hazard Communication Standard 29CFR1910.1200 as revised in May			

This SDS complies with the OSHA Hazard Communication Standard 29CFR1910.1200 as revised in May 2012 (GHS). It may not meet requirements in other countries.

SECTION 2 HAZARDS IDENTIFICATION

GHS Signal Word:	WARNING		
GHS Classification:	Skin Irritation (Category 2)		
GHS Hazard Statements:	Causes skin irritation		
GHS Precautionary Statements:	Prevention:	Response:	
	Wash hands/skin thoroughly after handling.	If on skin: Wash with plenty of water/soap.	
		If skin irritation occurs: Get medical	
	Wear protective gloves.	advice/attention.	
		Take off contaminated clothing and wash it before reuse.	
	Storage:	<u>Disposal:</u>	
	None.	None.	
Hazards Not Otherwise Classified:	None.		
GHS	Approximately < 4% of this mixture consists of ingredient(s) of unknown acute toxicity.		
Assessment:	Approximately < 4% of the mixture consists of ingredient(s) of unknown hazards to the aquatic environment.		

SECTION 3	COMPOSITION / INGREDIENTS
------------------	----------------------------------

SECTION 5 COMPOSITION / INCREDIENTS			
Component	CAS Number	EC Number	Concentration
Lubricating oils (petroleum), C20-50,	72623-87-1	276-738-4	20.0 - 40.0%
hydrotreated neutral oil	Classification: Carc. 1B: H350 (*) Carc. 1B; H350: C ≥ 3.0 % DMSO Repr. 2; H361d: C ≥ 3.0 % DMSO Asp. Tox. 1; H304: Viscosity ≤ 20.5 mm2/s (40°C)		
Petroleum distillates, hydrotreated heavy paraffinic	64742-54-7	265-157-1	20.0 - 40.0%
	Classification: Carc. 1B: H350 (*) Carc. 1B; H350: C ≥ 3.0 % DMSO Repr. 2; H361d: C ≥ 3.0 % DMSO Asp. Tox. 1; H304: Viscosity ≤ 20.5 mm2/s (40°C)		
Polyolefin	Proprietary		20.0 - 40.0%
	Clas	sification: Skin Irrit.	2: H315

Note (*): Components are highly refined and this hazard does not apply.

Other components are either non-hazardous or do not significantly contribute to the hazards of the product. Trade Secret Claims: Specific chemical identity and/or exact percentage (concentration) of components has been withheld as a trade secret.

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4 FIRST AID MEASURES

First Aid - Eyes:	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention, if irritation develops.
First Aid - Skin:	In case of contact, flush skin with plenty of soap and water while removing contaminated clothing and shoes. Get medical attention immediately if irritation develops and/or persists. Wash contaminated clothing before reuse.
First Aid - Ingestion:	If swallowed and feel unwell, immediately call a physician or poison control center. DO NOT induce vomiting unless directed to do so by a physician or poison control center. If victim is fully conscious, give a cupful of water. Never give anything by mouth to an unconscious person.
First Aid - Inhalation:	If respiratory symptoms or other symptoms of exposure develop, move victim away from source of exposure and into fresh air. If symptoms persist, seek immediate medical attention. If victim is not breathing, clear airway and immediately begin artificial respiration. If breathing difficulties develop, oxygen should be administered by qualified personnel. Seek immediate medical attention.
Important Symptoms / Effects – Acute and Delayed:	Tissue inflammation, nausea.
Advice to Physician:	Treat symptomatically.

SECTION 5 FIRE FIGHTING MEASURES

Extinguishing Media:	Treat surrounding material. Water spray, dry chemical, carbon dioxide, or foam is recommended. Carbon dioxide can displace oxygen. Use caution when applying carbon dioxide in confined spaces.
Specific Hazards:	This product is not flammable, but will burn in a fire. This product may give rise to hazardous vapors in a fire. Vapors/fumes may be irritating, corrosive and/or toxic.
Protective equipment and	Wear full protective clothing and self-contained breathing apparatus.

SECTION 5 FIRE FIGHTING MEASURES

procedures for fire-fighters.

Additional Advice: None.

SECTION 6 ACCIDENTAL RELEASE MEASURES

Spill Procedures:	Small spills: Wipe up spills with an absorbent towel/material and transfer into suitable containers for recovery or disposal. Finally flush area with water/soap or an appropriate solvent, as this product is not appreciably soluble in water alone.
	Large spills: Contain spilled material if possible. Pump into suitable and properly labeled containers.
Personal Precautions:	Wear suitable protective clothing and equipment.
Environmental Precautions:	Prevent the material from entering drains or water courses. Do not discharge directly to a water source. Advise Authorities if spillage has entered watercourse or sewer or has contaminated soil or vegetation.

SECTION 7 HANDLING AND STORAGE

Handling:	Wear appropriate personal protection (See Section 8) when handling this material. The work area should be equipped with a safety shower and eye wash station. If exposed to the liquid, avoid contact with skin and eyes. Wash thoroughly after handling. Avoid breathing vapors, mists or sprays. Use in a well-ventilated area.
Storage:	Keep container(s) tightly closed. Use and store this material at room temperature away from sources of ignition, heat, direct sunlight and hot metal surfaces. Keep away from any incompatible materials (see Section 10).
Additional Advice:	Store in original container. Store as directed by the manufacturer.

SECTION 8 EXPOSURE CONTROLS AND PERSONAL PROTECTION

Occupational Exposure Standards:	Exposure limits are listed below, if they exist.
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil:	(as petroleum distillates – naphtha) NIOSH REL: 350 mg/m3 TWA. NIOSH REL: 1800 mg/m3 STEL. OSHA PEL: 500 ppm (2000 mg/m3). (as oil mist) NIOSH REL: 5 mg/m3 TWA. NIOSH STEL: 10 mg/m3 TWA. OSHA PEL: 5 mg/m3 TWA.
Petroleum distillates, hydrotreated heavy paraffinic:	(as petroleum distillates – naphtha) NIOSH REL: 350 mg/m3 TWA. NIOSH REL: 1800 mg/m3 STEL. OSHA PEL: 500 ppm (2000 mg/m3). (as oil mist) NIOSH REL: 5 mg/m3 TWA. NIOSH STEL: 10 mg/m3 TWA. OSHA PEL: 5 mg/m3 TWA.
Polyolefin:	None.
Engineering Control Measures:	Engineering methods to prevent or control exposure are preferred. Methods include process or personnel enclosure, mechanical ventilation (local exhaust), and control of process conditions.

SECTION 8 EXPOSURE CONTROLS AND PERSONAL PROTECTION

Respiratory Protection:	A NIOSH certified self-contained breathing apparatus or air purifying respirator with an organic cartridge may be used under conditions where airborne concentrations are expected to exceed exposure limits.
Hand Protection:	The use of gloves impervious to the specific material handled is advised to prevent skin contact, possible irritation and skin damage (see glove manufacturer literature for information on permeability).
Eye Protection:	Approved eye protection (safety glasses with side-shields or goggles) to safeguard against potential eye contact, irritation, or injury is recommended. Depending on conditions of use, a face shield may be necessary.
Body Protection:	Impervious clothing should be worn as needed to prevent skin contact.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Physical State:	Liquid
Color:	Light to dark amber
Odor:	Characteristic
Odor Threshold:	Not available.
pH:	Not available.
Melting Point/Range (°C/°F):	-24.0°C / -11.2°F (pour point)
Boiling Point/Range (°C/°F):	> 200°C / 392°F (based on constituents)
Flash Point (PMCC) (°C/°F):	240.0°C / 464.0°F
Evaporation Rate:	Not available.
Flammability / Explosivity Limits in Air (%):	Not available.
Vapor Pressure:	< 0.075 mmHg (20°C) (based on constituents)
Vapor Density (Air = 1):	Not available.
Relative Density:	0.874 g/cm3 (15.6°C)
Solubility in Water:	Insoluble
Partition Coefficient:	Not available.
Autoignition Temperature (°C/°F):	> 250°C / 482°F (based on constituents)
Decomposition Temperature (°C/°F):	Not available.
Viscosity:	6800.0 mm2/s (40°C)
Explosive Properties:	None.
Oxidizing Properties:	None.
Volatile Organic Content (VOC) (g/l):	ca. 620 - 740 g/l (as defined by 40CFR51.100)

SECTION 10 STABILITY AND REACTIVITY

Reactivity:	Product will not undergo additional reaction.
Stability:	Stable under normal storage conditions.
Hazardous Polymerization:	Will not occur.
Conditions to Avoid:	Contact with incompatible materials, excessive heat.
Incompatibilities:	Strong oxidizing agents.

SECTION 10 STABILITY AND REACTIVITY

Hazardous Decomposition Products: Oxides of carbon, aliphatic and aromatic compounds, toxic by-products.

SECTION 11 TOXICOLOGICAL INFORMATION

If available, toxicity data for the product is given; otherwise component data is listed.

Acute Toxicity:	 This product is not expected to be appreciably harmful. (Lubricating oils (petroleum), C20-50, hydrotreated neutral oil) Oral LD50 (rat) > 5000 mg/kg (similar oil); Dermal LD50 (rat) > 5000 mg/kg (similar oil); Inhalation LC50 (rat) 2.18 mg/l (4 hr) (aerosol – similar oil) (Petroleum distillates, hydrotreated heavy paraffinic) Oral LD50 (rat) > 5000 mg/kg (similar oil); Dermal LD50 (rabbit) > 5000 mg/kg (similar oil); Inhalation LC50 (rat) > 5.53 mg/l (4 hr) (aerosol) (no mortality – similar oil) (Polyolefin) Oral LD50 (rat) > 10 g/kg; Dermal LD50 (rat) > 2000 mg/kg; Inhalation LC50 (rat) > 19171 mg/m3 (4 hr) (vapor)
Skin Corrosion / Irritation:	 The product may be irritating to the skin. (Lubricating oils (petroleum), C20-50, hydrotreated neutral oil) Slightly irritating to skin (rabbit – similar oil). (Petroleum distillates, hydrotreated heavy paraffinic) Mildly irritating to skin (rabbit – similar oil). (Polyolefin) Moderately irritating to skin (rabbit).
Serious Eye Damage / Irritation:	 The product may be slightly irritating to the eyes. (Lubricating oils (petroleum), C20-50, hydrotreated neutral oil) Slightly irritating to eye (rabbit – similar oil). (Petroleum distillates, hydrotreated heavy paraffinic) Non-irritating to eyes (rabbit – similar oil). (Polyolefin) Non-irritating to eye (rabbit).
Respiratory or Skin Sensitization:	 The product is not expected to be dermally sensitizing. (Lubricating oils (petroleum), C20-50, hydrotreated neutral oil) Not dermally sensitizing (guinea pig – similar oil). (Petroleum distillates, hydrotreated heavy paraffinic) Not dermally sensitizing (guinea pig – similar oil). (Polyolefin) Not dermally sensitizing (guinea pig).
Mutagenicity:	 This product is not expected to be mutagenic. (Lubricating oils (petroleum), C20-50, hydrotreated neutral oil) Not mutagenic (Ames test, in vitro mammalian chromosome aberration test, mammalian cell gene mutation assay and micronucleus assay – similar oils). (Petroleum distillates, hydrotreated heavy paraffinic) Not mutagenic (in vitro mammalian chromosome aberration test and micronucleus assay - similar oil). (Polyolefin) Not mutagenic (Amest test, in vitro mammalian chromosome
Carcinogenicity:	 aberration test and micronucleus assay). This product is not expected to be carcinogenic. (Lubricating oils (petroleum), C20-50, hydrotreated neutral oil) In a 78 week study in mice by dermal application (0.25 ml dose rate applied once or twice a week), it was shown that there was no carcinogenic potential in sufficiently refined oil. Not classified as to carcinogenicity to humans (IARC – Petroleum solvents). (Petroleum distillates, hydrotreated heavy paraffinic) Carcinogenic potential is reduced for highly refined distillates. Tumors have developed in animal studies, but were dependent on the concentration of impurities. Not classified as to carcinogenicity to humans (IARC – Petroleum solvents). (Polyolefin) No data.
Reproductive /	This product is not expected to be reproductively or developmentally harmful.

SECTION 11 TOXICOLOGICAL INFORMATION

Developmental Toxicity:	 (Lubricating oils (petroleum), C20-50, hydrotreated neutral oil) In dermally-exposed rats at up to 1000 mg/kg/day during gestation, the developmental NOAEL was determined to be 125 mg/kg/day based on decreased fetal body weights and skeletal anomalies at the highest dose (similar oil). (Petroleum distillates, hydrotreated heavy paraffinic) Reproductive performance and offspring development were not adversely affected in mice or rats (1000 mg/kg – similar oil). (Polyolefin) In orally-dosed rats at up to 1000 mg/kg/day, there were no significant signs of developmental toxicity (NOAEL was 1000 mg/kg/day).
Chronic/Subchronic Toxicity: Specific Target Organ/Systemic Toxicity – Single Exposure:	(Lubricating oils (petroleum), C20-50, hydrotreated neutral oil) No data. (Petroleum distillates, hydrotreated heavy paraffinic) No data. (Polyolefin) No data.
Chronic/Subchronic Toxicity: Specific Target Organ/Systemic Toxicity – Repeated Exposure:	 (Lubricating oils (petroleum), C20-50, hydrotreated neutral oil) In a 13-week oral study in rats at up to 500 mg/kg/day, the LOAEL was 125 mg/kg/day based on organ weight changes, reddening/discoloration of organs and atrophy in male sex organs (similar oil). (Petroleum distillates, hydrotreated heavy paraffinic) In a 13-week oral study in rats at up to 500 mg/kg/day, the LOAEL was 125 mg/kg/day based on organ weight changes, reddening/discoloration of organs and atrophy in rats at up to 500 mg/kg/day, the LOAEL was 125 mg/kg/day based on organ weight changes, reddening/discoloration of organs and atrophy in male sex organs (similar oil). (Polyolefin) In a 28-day oral study in rats at up to 1000 mg/kg/day, the NOAEL was determined to be 300 mg/kg/day based on increased liver and kidney weights at the highest dose.
Aspiration Hazard:	This product does not pose an appreciable aspiration hazard.
Additional Information:	None.

SECTION 12 ECOLOGICAL INFORMATION

If available, ecological data for the product is given; otherwise component data is listed.

Acute Ecotoxicity:	 This product is not expected to be appreciably harmful to aquatic species. (Lubricating oils (petroleum), C20-50, hydrotreated neutral oil) LL50 (fathead minnow) > 100 mg/l/96 hr; EL50 (Daphnia magna) > 10000 mg/l/48 hr; NOEL (algae) ≥ 100 mg/l/72 hr. (Petroleum distillates, hydrotreated heavy paraffinic) LL50 (Fathead minnow) > 100 mg/l/96 hr (similar oil); EL50 (Daphnia magna) > 10000 mg/l/48 hr (similar oil); NOEL (algae) > 100 mg/l/72 hr (similar oil). (Polyolefin) LC50 (ide) > 10 g/l/96 hr; LC50 (Daphnia magna) > 100 mg/l/48 hr; EC50 (blue-green algae) > 19.2 mg/l/72 hr.
Mobility:	 (Lubricating oils (petroleum), C20-50, hydrotreated neutral oil) Not expected to be mobile in soil. (Petroleum distillates, hydrotreated heavy paraffinic) Not expected to be mobile in soil. (Polyolefin) No data.
Persistence/Degradability:	 (Lubricating oils (petroleum), C20-50, hydrotreated neutral oil) Not readily biodegradable (2-4% in 28 days). (Petroleum distillates, hydrotreated heavy paraffinic) Not inherently biodegradable (2-4% in 28 days – similar oil). (Polyolefin) Readily biodegradable (93.9% in 28 days).
Bioaccumulation:	 (Lubricating oils (petroleum), C20-50, hydrotreated neutral oil) May contain constituents with the potential to bioaccumulate. (Petroleum distillates, hydrotreated heavy paraffinic) May contain constituents with the potential to bioaccumulate.

SECTION 12 ECOLOGICAL INFORMATION

(Polyolefin) No data.

Other adverse effects: None.

SECTION 13 DISPOSAL CONSIDERATION

Environmental precautions:	Prevent the material from entering drains or water courses. Do not discharge directly to a water source. Advise Authorities if spillage has entered watercourse or sewer or has contaminated soil or vegetation.
Product Disposal:	Dispose in accordance with all local, state (provincial), and federal regulations. Under RCRA, it is the responsibility of the product's user to determine at the time of disposal, whether the product meets RCRA criteria for hazardous waste. This is because the product uses, transformations, mixtures, processes, etc. may render the resulting materials hazardous.
Container Disposal:	Do not remove label until container is thoroughly cleaned. Empty containers may contain hazardous residues. This material and its container must be disposed of in a safe way.

SECTION 14 TRANSPORT INFORMATION

DOT (US):		
	Proper Shipping Name:	Not regulated
	UN Number:	None.
	Class:	None.
	Packaging Group:	None.
	Reportable Quantity:	None.
	Marine Pollutant:	None.
IAT	ΓA:	
	Proper Shipping Name:	Not regulated
	UN Number:	None.
	Class:	None.
	Packing Group:	None.
IMI	DG:	
	Proper Shipping Name:	Not regulated
	UN Number:	None.
	Class:	None.
	Packing Group:	None.
	Marine Pollutant:	None.

Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations.

SECTION 15 REGULATORY INFORMATION

US Toxic Substance Control	All components of this product are in compliance with the inventory
Act:	listing requirements of the U.S. Toxic Substances Control Act (TSCA)
	Chemical Substance Inventory.

SECTION 15 REGULATORY INFORMATION

Canadian Domestic Substance List:	All components of the Substance List.	nis product are listed on the Canadian Domestic	
EU REACh:	One or more components of this product may not have been pre-listed or registered under REACh. Limited quantities may be permitted.		
TSCA Sec.12(b) Export Notification:	This product does not contain a chemical at or above de minimis concentrations which requires reporting.		
Canadian WHMIS	D.2.B		
Classification:		en classified in accordance with the hazard criteria of DS contains all of the information required by the	
Massachusetts Right-To-Know:	Massachusetts Right - Lubricating oils (pe	etroleum), C20-50, hydrotreated neutral oil (as	
	petroleum distillates - Petroleum distillate distillates)	s) es, hydrotreated heavy paraffinic (as petroleum	
New Jersey Right-To-Know:	This product contain Jersey Right-To-Kn	ns materials subject to disclosure under the New	
	- Lubricating oils (pe	etroleum), C20-50, hydrotreated neutral oil (as	
	petroleum distillates) - Petroleum distillates, hydrotreated heavy paraffinic (as petroleum distillates)		
Pennsylvania Right-To-Know:	This product contain Pennsylvania Right	ns materials subject to disclosure under the -To-Know Law:	
		etroleum), C20-50, hydrotreated neutral oil (as	
		es, hydrotreated heavy paraffinic (as petroleum	
California Proposition 65:			
	- Propylene oxide (< 0.4 ppb) - Ethylene oxide (< 0.4 ppb)		
	- 1,4-Dioxane (< 0.4 ppb) - Toluene (< 22 ppm)		
	- Benzene (< 12 ppl		
SARA TITLE III-Section	Immediate (acute) h	nazard	
311/312 Categorization (40 CFR 370):	(as of 2018, the EPA has adopted GHS hazard classifications)		
SARA TITLE III-Section 313 (40 CFR 372):	This product does not contain materials which are listed in Section 313 at or above de minimis concentrations.		
CERCLA Hazardous Substance (40 CFR 302)	This product does not contain materials subject to reporting under CERCLA and Section 304 of EPCRA.		
Water Hazard Class (WGK):	This product is slightly water-endangering (WGK=1).		
Other Chemical Inventories:	Australia (AICS):	All components of the product are listed.	
	China (IECSC):	All components of the product are listed.	
	Japan (ENCS):	All components of the product are listed.	
	Korea (KCI):	All components of the product are listed.	

SECTION 15 REGULATORY INFORMATION

Philippines (PICCS): All components of the product are listed. Taiwan (TCSI):

One or more components are not listed.

SECTION 16 OTHER INFORMATION 1 NFPA Rating - HEALTH: NFPA Rating - FIRE: 1 NFPA Rating - REACTIVITY: 0 NFPA Rating - SPECIAL: NONE Full text of H-Statements referred to under Section 3: H304 May be fatal if swallowed and enters airways H350 May cause cancer H361 Suspected of damaging fertility or the unborn child H315 Causes skin irritation May 21, 2020 SDS Date Issued: SDS Current Version: 2.0 Version Date: October 25, 2021 SDS Revision History: v1.0 Initial version. v2.0 Revision based on changed formulation. Changes to physical properties (Section 9) and California Proposition 65 (Section 15). Abbreviations: GHS: Globally Harmonized System of Classification and Labeling of Chemicals CAS#: Chemical Abstract Services Number ACGIH: American Conference of Governmental Industrial Hygienists OSHA: Occupational Safety and Health Administration National Fire Protection Association NFPA: DOT: US Department of Transportation US Resource Conservation and Recovery Act RCRA: TLV: Threshold Limit Value Time-Weighted Average TWA: Permissible Exposure Limit PEL: Short Term Exposure Limit STEL: WEEL: Workplace Environmental Exposure Levels AIHA: American Industrial Hygiene Association NTP: National Toxicology Program IARC: International Agency for Research on Cancer LD50: Lethal Dose 50% Lethal Concentration 50% LC50: NOAEL: No Observed Adverse Effect Level No Observed Effect Level NOEL: EC50: Effective Concentration 50% Lethal Loading Rate 50% LL50: **Bioconcentration Factor** BCF BOD: **Biological Oxygen Demand** Koc: Soil Organic Carbon Partition Coefficient. TIm: Median Tolerance Limit United States National Library of Medicine's TOXNET Key References:

SECTION 16 OTHER INFORMATION

	United States Occupational Safety and Health Administration United States Department of Transportation Supplier Material Safety Data Sheets
Disclaimer:	The data contained herein is based on information that the company believes to be reliable, but no expressed or implied warranty is made with regard to the accuracy of such data or its suitability for a given situation. Such data relates only to the specific product described and not to such products in combination with any other product and no agent of the company is authorized to vary any of such data. The company and its agents disclaim all liability for any action taken or foregone on reliance upon such data.
Prepared by:	ChemOne Compliance, LLC