



Synplus Synthetic Blend 2T Motorcycle Oil

(October 2021 edition)

AMALIE Synplus Synthetic Blend 2T Motorcycle Oil is a synthetic blend lubricant formulated for high performance air-cooled 2-cycle motorcycle engines. It protects against high-temperature oxidation and corrosion while also ensuring cleanliness. This is a low ash formulation that prevents carbon deposit build-up on engine parts, and protects against ring sticking. This oil is formulated with high-temperature performance chemistry and special smoke reducing components to give you the ultimate in engine protection and environmental performance. These oils may be used in other air-cooled applications, such as snowmobiles, lawn mowers, string trimmers, air-blowers, snow blowers, all-terrain vehicles and many others requiring API service category TC, ISO-L-EGC, EGD and JASO FC, FD.

Benefits

- Formulated with a Blend of Premium Synthetic and Conventional Base Stocks
- Low-Ash Chemistry
- Smoke Reducing Additives Protect the Environment
- Protects Against Wear and Corrosion

Typical Physical and Chemical Properties

Viscosity Grade.....	SAE 20W-20
Kinematic Viscosity @100°C, cSt.....	7.0
Kinematic Viscosity @40°C, cSt.....	42.0
Viscosity Index.....	135
Sulfated Ash, Mass %.....	0.08
Flash Point, °C (°F).....	200 (392)
Pour Point, °C (°F).....	-24 (-11.2)
Visual Color.....	Red
API Gravity.....	32.5

Typical values are listed. Variations not affecting the performance of this fluid may occur during production however; these variations will not fall outside of set specification parameters.

Health and Safety

Safety Data Sheets (SDS) are available from your sales representative or at AMALIE.com.