



Xtreme 4T Motorcycle 10W-40

(September 2021 edition)

AMALIE Xtreme 4T Motorcycle 10W-40 is designed to provide wear protection, sludge and varnish protection, and thermal stability for superior performance in four-cycle motorcycle applications. Blended with high-quality base stocks and performance chemistry; the **AMALIE Xtreme 4T Motorcycle 10W-40** is formulated for superior operation in high-revving, high-temperature motorcycle engines and is blended to give superior performance in those engines and transmissions that have a common sump and require specialized frictional characteristics for clutches and wet brakes. The **AMALIE Xtreme 4T Motorcycle 10W-40** meets or exceeds the API SG and JASO MA categories.

Benefits

- Outstanding Thermal and Oxidation Stability
- Excellent Sludge and Varnish Protection
- Volatility: Lowers Oil Vaporization and Consumption at Extreme Conditions
- Excellent Wear Protection
- Outstanding Frictional Characteristics

Typical Physical and Chemical Properties

Viscosity Grade.....	SAE 10W-40
Kinematic Viscosity @100°C, cSt.....	13.5
Kinematic Viscosity @40°C, cSt.....	91.65
Viscosity Index.....	150
Cold Cranking Viscosity, cP @ -25 (°C)	5500
Flash Point, °C (°F).....	220 (428)
Pour Point, °C (°F).....	-33 (-27.4)
HT/HS Viscosity, cP.....	3.7
TBN, mgKOH/gram.....	5.0

Typical values are listed. Variations not affecting the performance of this fluid may occur during production; however, these variations will not fall outside of set specification parameters.

Health and Safety

Safety Data Sheets (SDS) are available online at AMALIE.com or from your AMALIE Representative.