

AMALIE®

Better than it has to be®
Since 1903

WATER / GLYCOL FIRE RESISTANT FLUID

AMALIE Water / Glycol Fire Resistant Fluid is a fully formulated water/glycol hydraulic fluid which contains a special anti-wear package and other additives to prevent ferrous and non-ferrous metal corrosion. It will also provide vapor phase corrosion protection and reserve alkalinity. This is a premium water/glycol type of fire-resistant fluid designed to provide optimum performance in hydraulic systems. **AMALIE Water / Glycol Fire Resistant Fluid** is formulated to provide excellent service over a wide range of operating conditions. In addition to its excellent fire-resistant properties, this fluid contains additive chemistry which imparts antiwear properties, lubricity, corrosion protection, form inhibition, and overall performance demanded by today's high-performance hydraulic systems. This achieved through a diethylene-glycol based water mixture. This fluid is suitable for use in most hydraulic applications and where the following are called for or referenced:

- Factory Mutual
- US Steel 17
- Vickers 104C Vane Pump Test, ASTM D 2882, result <50 mg total wear
- Four Ball Wear, ASTM D 2266, < 0.7 mm.

TRANSFORMER OIL

AMALIE Transformer Oil is an insulating oil of very high dielectric strength, suited for transformers in both large sub-stations and small pole mounted transformers. It is also suited for circuit breakers, switches and other oil immersed electrical equipment. **AMALIE Transformer Oil** is suitable for applications where the following are called for or referenced:

- ASTM D 3487 type II (oxidation inhibited oils)
- Westinghouse PDS 55822A
- Does not contain PCB's

FORM OIL

AMALIE Form Oil is a multipurpose mold release oil primarily used to ease the release of concrete mold materials. This oil contains special mold release agents to enhance the separation, release, and clean up of metal, wood, plastics or other types of forms. **AMALIE Form Oil** is a low viscosity formulation which is colorless, odorless, and may be sprayed without dilution.

Benefits:

- Excellent release characteristics from the poured material
- Reduces buildup on forms
- Non-staining
- Easy to apply in all types of weather temperatures

MADE IN U.S.A.



WATER / GLYCOL FIRE RESISTANT FLUID

VISCOSITY	PACK SIZE	PART #
	55 Gallon Drum	160-68173-05

TRANSFORMER OIL

VISCOSITY	PACK SIZE	PART #
	55 Gallon Drum	160-68063-05

FORM OIL

VISCOSITY	PACK SIZE	PART #
70	55 Gallon Drum	160-67673-05

Always refer to your vehicles operating manual to select the correct grade of oil for your engine. The data presented herein are believed to be accurate; however, Amalie Oil Company shall not be liable for its content and makes no warranty with respect thereto.